

UNMANAGED INDUSTRIAL (PoE) ETHERNET SWITCH

FR-7N3008

Main Features

- 8x10/100/1000BASE-T RJ45
- -40°C~75°C OT
- Dual DC9-56V
- Jumbo Frame up to 10K
- 20G backplane bandwidth
- Full/Half-duplex self-adaptation



Overview


- Easy to Maintenance
- High Reliability and Stability
- Heat Resistant
- Reliable Performance
- Resilient to Extreme Conditions



Specifications

Hardware Features	
Product	FR-7N3008
Ports	8x10/100/1000Base-TX Port(RJ45)
Exchange Property	Delay time: < 7μs Backplane bandwidth: 20G
Transmission Mode	Store-and-Forward
Dimensions	138mm x 108mm x 49mm (L x W x H)
Operating Temperature	-40°C~75°C (-40 to 167 °F)
Storage Temperature	-40~85°C(-40 to 185°F)
Operating Humidity	5%~90% (non-condensing)
Power Consumption	Full-load<15W

Dimensions



Address:
B-G-3A, Endah Promenade No. 5,
Jalan 3/149E, Taman Sri Endah,
Sri Petaling, 57000 Kuala Lumpur.



018-3366566



Sentinel Systems Sdn Bhd



sales@sentinel systems.com.my